Cygwin API Reference

Copyright © Cygwin authors

Permission is granted to make and distribute verbatim copies of this documentation provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this documentation under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this documentation into another language, under the above conditions for modified versions, except that this permission notice may be stated in a translation approved by the Free Software Foundation.

Contents

1 Compatibility **1**

1.1 System interfaces compatible with the Single UNIX® Specification Version 5: . . . 1
1.2 System interfaces compatible with BSD functions: . . . 21
1.3 System interfaces compatible with GNU or Linux extensions: . . . 23
1.4 System interfaces compatible with Solaris or SunOS functions: . . . 25
1.5 System interfaces not in POSIX but compatible with ISO C requirements: . . . 26
1.6 Other UNIX® system interfaces, not in POSIX.1-2024, or deprecated: . . . 26
1.7 NOT implemented system interfaces from the Single UNIX® Specification Version 5: . . . 28
1.8 Other system interfaces, some from Windows: . . . 29
1.9 Implementation Notes . . . 29

2 Cygwin Functions **32**

2.1 Path conversion functions . . . 32
2.1.1 cygwin_conv_path . . . 32
2.1.2 cygwin_conv_path_list . . . 33
2.1.3 cygwin_create_path . . . 33
2.1.4 cygwin_posix_path_list_p . . . 34
2.1.5 cygwin_split_path . . . 34
2.2 Helper functions to change user context . . . 35
2.2.1 cygwin_logon_user . . . 35
2.2.2 cygwin_set_impersonation_token . . . 35
2.3 Miscellaneous functions . . . 36
2.3.1 cygwin_attach_handle_to_fd . . . 36
2.3.2 cygwin_internal . . . 36
2.3.3 cygwin_stackdump . . . 36

Abstract

Cygwin API Reference

Chapter 1

Compatibility

1.1 System interfaces compatible with the Single UNIX® Specification Version 5:

Note that the core of the Single UNIX® Specification Version 5 is POSIX®.1-2024 also simultaneously IEEE Std 1003.1™-2024 Edition, The ®Open Group Base Specifications Issue 8 (see https://pubs.opengroup.org/onlinepubs/9799919799/), and ISO®/IEC DIS 9945 Information technology - Portable Operating System Interface (POSIX®) base specifications - Issue 8.

```
CMPLX
CMPLXF
CMPLXL
FD_CLR
FD_ISSET
FD_SET
FD_ZERO
_Exit
_exit
a64l
abort
abs
accept
accept4
access
acos
acosf
acosh
acoshf
acoshl
acosl
aio_cancel
aio_error
aio_fsync
aio_read
aio_return
aio_suspend
aio_write
alarm
aligned_alloc
alphasort
asctime
asctime_r
asin
asinf
asinh
asinhf
```

```
asinhl
asinl
asprintf
assert
at_quick_exit
atan
atan2
atan2f
atan2l
atanf
atanh
atanhf
atanhl
atanl
atexit
atof
atoi
atol
atoll
atomic_compare_exchange_strong
atomic_compare_exchange_strong_explicit
atomic_compare_exchange_weak
atomic_compare_exchange_weak_explicit
atomic_exchange
atomic_exchange_explicit
atomic_fetch_add
atomic_fetch_add_explicit
atomic_fetch_and
atomic_fetch_and_explicit
atomic_fetch_or
atomic_fetch_or_explicit
atomic_fetch_sub
atomic_fetch_sub_explicit
atomic_fetch_xor
atomic_fetch_xor_explicit
atomic_flag_clear
atomic_flag_clear_explicit
atomic_flag_test_and_set
atomic_flag_test_and_set_explicit
atomic_init
atomic_is_lock_free
atomic_load
atomic_load_explicit
atomic_signal_fence
atomic_store
atomic_store_explicit
atomic_thread_fence
basename      (see chapter "Implementation Notes")
be16toh
be32toh
be64toh
bind
bind_textdomain_codeset
bindtextdomain
bsearch
btowc
c16rtomb
c32rtomb
cabs
cabsf
cabsl
cacos
```

```
    cacosf
    cacosh
    cacoshf
    cacoshl
    cacosl
    call_once
    calloc
    carg
    cargf
    cargl
    casin
    casinf
    casinh
    casinhf
    casinhl
    casinl
    catan
    catanf
    catanh
    catanhf
    catanhl
    catanl
    catclose
    catgets
    catopen
    cbrt
    cbrtf
    cbrtl
    ccos
    ccosf
    ccosh
    ccoshf
    ccoshl
    ccosl
    ceil
    ceilf
    ceill
    cexp
    cexpf
    cexpl
    cfgetispeed
    cfgetospeed
    cfsetispeed
    cfsetospeed
    chdir
    chmod
    chown
    cimag
    cimagf
    cimagl
    clearerr
    clock
    clock_getcpuclockid
    clock_getres
    clock_gettime
    clock_nanosleep   (see chapter "Implementation Notes")
    clock_settime   (see chapter "Implementation Notes")
    clog
    clogf
    clogl
    close
    closedir
```

```
    closelog
    cnd_broadcast
    cnd_destroy
    cnd_init
    cnd_signal
    cnd_timedwait
    cnd_wait
    confstr
    conj
    conjf
    conjl
    connect
    copysign
    copysignf
    copysignl
    cos
    cosf
    cosh
    coshf
    coshl
    cosl
    cpow
    cpowf
    cpowl
    cproj
    cprojf
    cprojl
    creal
    crealf
    creall
    creat
    crypt     (available in external "libcrypt" library)
    csin
    csinf
    csinh
    csinhf
    csinhl
    csinl
    csqrt
    csqrtf
    csqrtl
    ctan
    ctanf
    ctanh
    ctanhf
    ctanhl
    ctanl
    ctermid
    ctime
    ctime_r
    daylight
    dbm_clearerr    (available in external "libgdbm" library)
    dbm_close     (available in external "libgdbm" library)
    dbm_delete      (available in external "libgdbm" library)
    dbm_error     (available in external "libgdbm" library)
    dbm_fetch     (available in external "libgdbm" library)
    dbm_firstkey    (available in external "libgdbm" library)
    dbm_nextkey     (available in external "libgdbm" library)
    dbm_open      (available in external "libgdbm" library)
    dbm_store     (available in external "libgdbm" library)
    dcgettext     (available in external "libintl" library)
    dcngettext      (available in external "libintl" library)
```

```
dgettext      (available in external "libintl" library)
difftime
dirfd
dirname
div
dladdr      (see chapter "Implementation Notes")
dlclose
dlerror
dlopen
dlsym
dngettext     (available in external "libintl" library)
dprintf
drand48
dup
dup2
dup3
duplocale
encrypt     (available in external "libcrypt" library)
endgrent
endhostent
endprotoent
endpwent
endservent
endutxent
environ
erand48
erf
erfc
erfcf
erfcl
erff
erfl
errno
execl
execle
execlp
execv
execve
execvp
exit
exp
exp2
exp2f
exp2l
expf
expl
expm1
expm1f
expm1l
fabs
fabsf
fabsl
faccessat
fchdir
fchmod
fchmodat
fchown
fchownat
fclose
fcntl     (see chapter "Implementation Notes")
fdatasync
fdim
```

```
    fdimf
    fdiml
    fdopen
    fdopendir
    feclearexcept
    fegetenv
    fegetexceptflag
    fegetround
    feholdexcept
    feof
    feraiseexcept
    ferror
    fesetenv
    fesetexceptflag
    fesetround
    fetestexcept
    feupdateenv
    fexecve
    fflush
    ffs
    ffsl
    ffsll
    fgetc
    fgetpos
    fgets
    fgetwc
    fgetws
    fileno
    flockfile
    floor
    floorf
    floorl
    fma
    fmaf
    fmal
    fmax
    fmaxf
    fmaxl
    fmemopen
    fmin
    fminf
    fminl
    fmod
    fmodf
    fmodl
    fnmatch
    fopen
    fork
    fpathconf
    fpclassify      (see chapter "Implementation Notes")
    fprintf
    fputc
    fputs
    fputwc
    fputws
    fread
    free
    freeaddrinfo
    freelocale
    freopen
    frexp
    frexpf
```

```
    frexpl
    fscanf
    fseek
    fseeko
    fsetpos
    fstat
    fstatat
    fstatvfs
    fsync
    ftell
    ftello
    ftok
    ftruncate
    ftrylockfile
    funlockfile
    futimens
    fwide
    fwprintf
    fwrite
    fwscanf
    gai_strerror
    getaddrinfo
    getc
    getc_unlocked
    getchar
    getchar_unlocked
    getcwd
    getdelim
    getegid
    getentropy
    getenv
    geteuid
    getgid
    getgrent
    getgrgid
    getgrgid_r
    getgrnam
    getgrnam_r
    getgroups
    gethostid
    gethostname
    getline
    getlocalename_l
    getlogin
    getlogin_r
    getnameinfo
    getopt
    getpeername
    getpgid
    getpgrp
    getpid
    getppid
    getpriority
    getprotobyname
    getprotobynumber
    getprotoent
    getpwent
    getpwnam
    getpwnam_r
    getpwuid
    getpwuid_r
    getrlimit     (see chapter "Implementation Notes")
```

```
    getrusage
    getservbyname
    getservbyport
    getservent
    getsid
    getsockname
    getsockopt
    getsubopt
    gettext     (available in external "libintl" library)
    getuid
    getutxent
    getutxid
    getutxline
    getwc
    getwchar
    glob
    globfree
    gmtime
    gmtime_r
    grantpt
    hcreate
    hdestroy
    hsearch
    htobe16
    htobe32
    htobe64
    htole16
    htole32
    htole64
    htonl
    htons
    hypot
    hypotf
    hypotl
    iconv     (available in external "libiconv" library)
    iconv_close     (available in external "libiconv" library)
    iconv_open      (available in external "libiconv" library)
    if_freenameindex
    if_indextoname
    if_nameindex
    if_nametoindex
    ilogb
    ilogbf
    ilogbl
    imaxabs
    imaxdiv
    in6addr_any
    in6addr_loopback
    inet_addr
    inet_ntoa
    inet_ntop
    inet_pton
    initstate
    insque
    isalnum
    isalnum_l
    isalpha
    isalpha_l
    isatty
    isblank
    isblank_l
    iscntrl
```

```
iscntrl_l
isdigit
isdigit_l
isfinite      (see chapter "Implementation Notes")
isgraph
isgraph_l
isgreater     (see chapter "Implementation Notes")
isgreaterequal    (see chapter "Implementation Notes")
isinf     (see chapter "Implementation Notes")
isless
islessequal     (see chapter "Implementation Notes")
islessgreater   (see chapter "Implementation Notes")
islower
islower_l
isnan     (see chapter "Implementation Notes")
isnormal      (see chapter "Implementation Notes")
isprint
isprint_l
ispunct
ispunct_l
isspace
isspace_l
isunordered     (see chapter "Implementation Notes")
isupper
isupper_l
iswalnum
iswalnum_l
iswalpha
iswalpha_l
iswblank
iswblank_l
iswcntrl
iswcntrl_l
iswctype
iswctype_l
iswdigit
iswdigit_l
iswgraph
iswgraph_l
iswlower
iswlower_l
iswprint
iswprint_l
iswpunct
iswpunct_l
iswspace
iswspace_l
iswupper
iswupper_l
iswxdigit
iswxdigit_l
isxdigit
isxdigit_l
j0
j1
jn
jrand48
kill
kill_dependency
killpg
l64a
labs
```

```
    lchown
    lcong48
    ldexp
    ldexpf
    ldexpl
    ldiv
    le16toh
    le32toh
    le64toh
    lfind
    lgamma
    lgammaf
    lgammal
    link
    linkat
    lio_listio
    listen
    llabs
    lldiv
    llrint
    llrintf
    llrintl
    llround
    llroundf
    llroundl
    localeconv
    localtime
    localtime_r
    lockf     (see chapter "Implementation Notes")
    log
    log10
    log10f
    log10l
    log1p
    log1pf
    log1pl
    log2
    log2f
    log2l
    logb
    logbf
    logbl
    logf
    logl
    longjmp
    lrand48
    lrint
    lrintf
    lrintl
    lround
    lroundf
    lroundl
    lsearch
    lseek
    lstat
    malloc
    mblen
    mbrlen
    mbrtoc16
    mbrtoc32
    mbrtowc
    mbsinit
```

```
    mbsnrtowcs
    mbsrtowcs
    mbstowcs
    mbtowc
    memccpy
    memchr
    memcmp
    memcpy
    memmem
    memmove
    memset
    mkdir
    mkdirat
    mkdtemp
    mkfifo
    mkfifoat
    mknod
    mknodat
    mkostemp
    mkstemp
    mktime
    mlock
    mmap
    modf
    modff
    modfl
    mprotect
    mq_close
    mq_getattr
    mq_notify
    mq_open
    mq_receive
    mq_send
    mq_setattr
    mq_timedreceive
    mq_timedsend
    mq_unlink
    mrand48
    msgctl      (see chapter "Implementation Notes")
    msgget      (see chapter "Implementation Notes")
    msgrcv      (see chapter "Implementation Notes")
    msgsnd      (see chapter "Implementation Notes")
    msync
    mtx_destroy
    mtx_init
    mtx_lock
    mtx_timedlock
    mtx_trylock
    mtx_unlock
    munlock
    munmap
    nan
    nanf
    nanl
    nanosleep
    nearbyint
    nearbyintf
    nearbyintl
    newlocale
    nextafter
    nextafterf
    nextafterl
```

```
nexttoward
nexttowardf
nexttowardl
nftw
ngettext      (available in external "libintl" library)
nice      (see chapter "Implementation Notes")
nl_langinfo
nl_langinfo_l
nrand48
ntohl
ntohs
open
open_memstream
open_wmemstream
openat
opendir
openlog
optarg
opterr
optind
optopt
pathconf
pause
pclose
perror
pipe
pipe2
poll
popen
posix_close
posix_devctl
posix_fadvise
posix_fallocate
posix_getdents
posix_madvise
posix_memalign
posix_openpt
posix_spawn
posix_spawn_file_actions_addchdir
posix_spawn_file_actions_addclose
posix_spawn_file_actions_adddup2
posix_spawn_file_actions_addfchdir
posix_spawn_file_actions_addopen
posix_spawn_file_actions_destroy
posix_spawn_file_actions_init
posix_spawnattr_destroy
posix_spawnattr_getflags
posix_spawnattr_getpgroup
posix_spawnattr_getschedparam
posix_spawnattr_getschedpolicy
posix_spawnattr_getsigdefault
posix_spawnattr_getsigmask
posix_spawnattr_init
posix_spawnattr_setflags
posix_spawnattr_setpgroup
posix_spawnattr_setschedparam
posix_spawnattr_setschedpolicy
posix_spawnattr_setsigdefault
posix_spawnattr_setsigmask
posix_spawnp
pow
powf
```

```
    powl
    ppoll
    pread
    printf
    pselect
    psiginfo
    psignal
    pthread_atfork
    pthread_attr_destroy
    pthread_attr_getdetachstate
    pthread_attr_getguardsize
    pthread_attr_getinheritsched
    pthread_attr_getschedparam
    pthread_attr_getschedpolicy
    pthread_attr_getscope
    pthread_attr_getstack
    pthread_attr_getstacksize
    pthread_attr_init
    pthread_attr_setdetachstate
    pthread_attr_setguardsize
    pthread_attr_setinheritsched
    pthread_attr_setschedparam
    pthread_attr_setschedpolicy
    pthread_attr_setscope
    pthread_attr_setstack
    pthread_attr_setstacksize
    pthread_barrier_destroy
    pthread_barrier_init
    pthread_barrier_wait
    pthread_barrierattr_destroy
    pthread_barrierattr_getpshared
    pthread_barrierattr_init
    pthread_barrierattr_setpshared
    pthread_cancel
    pthread_cleanup_pop
    pthread_cleanup_push
    pthread_cond_broadcast
    pthread_cond_clockwait
    pthread_cond_destroy
    pthread_cond_init
    pthread_cond_signal
    pthread_cond_timedwait
    pthread_cond_wait
    pthread_condattr_destroy
    pthread_condattr_getclock
    pthread_condattr_getpshared
    pthread_condattr_init
    pthread_condattr_setclock
    pthread_condattr_setpshared
    pthread_create
    pthread_detach
    pthread_equal
    pthread_exit
    pthread_getcpuclockid
    pthread_getschedparam
    pthread_getspecific
    pthread_join
    pthread_key_create
    pthread_key_delete
    pthread_kill
    pthread_mutex_clocklock
    pthread_mutex_destroy
```

```
    pthread_mutex_getprioceiling
    pthread_mutex_init
    pthread_mutex_lock
    pthread_mutex_setprioceiling
    pthread_mutex_timedlock
    pthread_mutex_trylock
    pthread_mutex_unlock
    pthread_mutexattr_destroy
    pthread_mutexattr_getprioceiling
    pthread_mutexattr_getprotocol
    pthread_mutexattr_getpshared
    pthread_mutexattr_gettype
    pthread_mutexattr_init
    pthread_mutexattr_setprioceiling
    pthread_mutexattr_setprotocol
    pthread_mutexattr_setpshared
    pthread_mutexattr_settype
    pthread_once
    pthread_rwlock_clockrdlock
    pthread_rwlock_clockwrlock
    pthread_rwlock_destroy
    pthread_rwlock_init
    pthread_rwlock_rdlock
    pthread_rwlock_timedrdlock
    pthread_rwlock_timedwrlock
    pthread_rwlock_tryrdlock
    pthread_rwlock_trywrlock
    pthread_rwlock_unlock
    pthread_rwlock_wrlock
    pthread_rwlockattr_destroy
    pthread_rwlockattr_getpshared
    pthread_rwlockattr_init
    pthread_rwlockattr_setpshared
    pthread_self
    pthread_setcancelstate
    pthread_setcanceltype
    pthread_setschedparam
    pthread_setschedprio
    pthread_setspecific
    pthread_sigmask
    pthread_spin_destroy
    pthread_spin_init
    pthread_spin_lock
    pthread_spin_trylock
    pthread_spin_unlock
    pthread_testcancel
    ptsname
    ptsname_r
    putc
    putc_unlocked
    putchar
    putchar_unlocked
    putenv
    puts
    pututxline
    putwc
    putwchar
    pwrite
    qsort
    qsort_r     (see chapter "Implementation Notes")
    quick_exit
    raise
```

```
    rand
    random
    read
    readdir
    readdir_r
    readlink
    readlinkat
    readv
    realloc
    reallocarray
    realpath
    recv
    recvfrom
    recvmsg
    regcomp
    regerror
    regexec
    regfree
    remainder
    remainderf
    remainderl
    remove
    remque
    remquo
    remquof
    remquol
    rename
    renameat
    rewind
    rewinddir
    rint
    rintf
    rintl
    rmdir
    round
    roundf
    roundl
    scalbln
    scalblnf
    scalblnl
    scalbn
    scalbnf
    scalbnl
    scandir
    scanf
    sched_get_priority_max
    sched_get_priority_min
    sched_getparam
    sched_getscheduler
    sched_rr_get_interval
    sched_setparam    (see chapter "Implementation Notes")
    sched_setscheduler    (see chapter "Implementation Notes")
    sched_yield
    secure_getenv
    seed48
    seekdir
    select
    sem_clockwait
    sem_close
    sem_destroy
    sem_getvalue
    sem_init
```

```
sem_open
sem_post
sem_timedwait
sem_trywait
sem_unlink
sem_wait
semctl      (see chapter "Implementation Notes")
semget      (see chapter "Implementation Notes")
semop     (see chapter "Implementation Notes")
send
sendmsg
sendto
setbuf
setegid
setenv
seteuid
setgid
setgrent
sethostent
setjmp
setkey      (available in external "libcrypt" library)
setlocale
setlogmask
setpgid
setpriority     (see chapter "Implementation Notes")
setprotoent
setpwent
setregid
setreuid
setrlimit     (see chapter "Implementation Notes")
setservent
setsid
setsockopt
setstate
setuid
setutxent
setvbuf
shm_open
shm_unlink
shmat     (see chapter "Implementation Notes")
shmctl      (see chapter "Implementation Notes")
shmdt     (see chapter "Implementation Notes")
shmget      (see chapter "Implementation Notes")
shutdown
sig2str
sigaction
sigaddset
sigaltstack
sigdelset
sigemptyset
sigfillset
sigismember
siglongjmp
signal
signbit     (see chapter "Implementation Notes")
signgam
sigpending
sigprocmask
sigqueue
sigsetjmp
sigsuspend
sigtimedwait
```

```
    sigwait
    sigwaitinfo
    sin
    sinf
    sinh
    sinhf
    sinhl
    sinl
    sleep
    snprintf
    sockatmark
    socket
    socketpair
    sprintf
    sqrt
    sqrtf
    sqrtl
    srand
    srand48
    srandom
    sscanf
    stat
    statvfs
    stderr
    stdin
    stdout
    stpcpy
    stpncpy
    str2sig
    strcasecmp
    strcasecmp_l
    strcat
    strchr
    strcmp
    strcoll
    strcoll_l
    strcpy
    strcspn
    strdup
    strerror
    strerror_l
    strerror_r      (see chapter "Implementation Notes")
    strfmon
    strfmon_l
    strftime
    strftime_l
    strlcat
    strlcpy
    strlen
    strncasecmp
    strncasecmp_l
    strncat
    strncmp
    strncpy
    strndup
    strnlen
    strpbrk
    strptime
    strrchr
    strsignal
    strspn
    strstr
```

```
    strtod
    strtof
    strtoimax
    strtok
    strtok_r
    strtol
    strtold
    strtoll
    strtoul
    strtoull
    strtoumax
    strxfrm
    strxfrm_l
    swab
    swprintf
    swscanf
    symlink
    symlinkat
    sync
    sysconf
    syslog
    system
    tan
    tanf
    tanh
    tanhf
    tanhl
    tanl
    tcdrain
    tcflow
    tcflush
    tcgetattr
    tcgetpgrp
    tcgetsid
    tcgetwinsize
    tcsendbreak
    tcsetattr
    tcsetpgrp
    tcsetwinsize
    tdelete
    telldir
    textdomain      (available in external "libintl" library)
    tfind
    tgamma
    tgammaf
    tgammal
    thrd_create
    thrd_current
    thrd_detach
    thrd_equal
    thrd_exit
    thrd_join
    thrd_sleep
    thrd_yield
    time
    timer_create    (see chapter "Implementation Notes")
    timer_delete
    timer_getoverrun
    timer_gettime
    timer_settime
    times
    timespec_get
```

```
    timezone
    tmpfile
    tmpnam
    tolower
    tolower_l
    toupper
    toupper_l
    towctrans
    towctrans_l
    towlower
    towlower_l
    towupper
    towupper_l
    trunc
    truncate
    truncf
    truncl
    tsearch
    tss_create
    tss_delete
    tss_get
    tss_set
    ttyname
    ttyname_r
    twalk
    tzname
    tzset
    umask
    uname
    ungetc
    ungetwc
    unlink
    unlinkat
    unlockpt
    unsetenv
    uselocale
    utimensat
    utimes
    va_arg
    va_copy
    va_end
    va_start
    vasprintf
    vdprintf
    vfprintf
    vfscanf
    vfwprintf
    vfwscanf
    vprintf
    vscanf
    vsnprintf
    vsprintf
    vsscanf
    vswprintf
    vswscanf
    vwprintf
    vwscanf
    wait
    waitpid
    wcpcpy
    wcpncpy
    wcrtomb
```

```
    wcscasecmp
    wcscasecmp_l
    wcscat
    wcschr
    wcscmp
    wcscoll
    wcscoll_l
    wcscpy
    wcscspn
    wcsdup
    wcsftime
    wcslcat
    wcslcpy
    wcslen
    wcsncasecmp
    wcsncasecmp_l
    wcsncat
    wcsncmp
    wcsncpy
    wcsnlen
    wcsnrtombs
    wcspbrk
    wcsrchr
    wcsrtombs
    wcsspn
    wcsstr
    wcstod
    wcstof
    wcstoimax
    wcstok
    wcstol
    wcstold
    wcstoll
    wcstombs
    wcstoul
    wcstoull
    wcstoumax
    wcswidth
    wcsxfrm
    wcsxfrm_l
    wctob
    wctomb
    wctrans
    wctrans_l
    wctype
    wctype_l
    wcwidth
    wmemchr
    wmemcmp
    wmemcpy
    wmemmove
    wmemset
    wordexp
    wordfree
    wprintf
    write
    writev
    wscanf
    y0
    y1
    yn
```

1.2 System interfaces compatible with BSD functions:

```
__b64_ntop
__b64_pton
arc4random
arc4random_addrandom
arc4random_buf
arc4random_stir
arc4random_uniform
bindresvport
bindresvport_sa
cfmakeraw
cfsetspeed
clearerr_unlocked
close_range
daemon
dn_comp
dn_expand
dn_skipname
drem
eaccess
endusershell
err
errx
explicit_bzero
feof_unlocked
ferror_unlocked
fflush_unlocked
fgetc_unlocked
fileno_unlocked
finite
finitef
finitel
fiprintf
flock     (see chapter "Implementation Notes")
fls
flsl
flsll
forkpty
fpurge
fputc_unlocked
fread_unlocked
freeifaddrs
fstatfs
fts_children
fts_close
fts_get_clientptr
fts_get_stream
fts_open
fts_read
fts_set
fts_set_clientptr
funopen
futimes
fwrite_unlocked
gamma
gamma_r
gammaf
gammaf_r
getdomainname
getdtablesize
```

```
    getgrouplist
    getifaddrs
    getloadavg
    getpagesize
    getpeereid
    getprogname
    getusershell
    herror
    hstrerror
    inet_aton
    inet_makeaddr
    inet_netof
    inet_network
    initgroups
    iruserok
    iruserok_sa
    issetugid
    login
    login_tty
    logout
    logwtmp
    madvise
    mkstemps
    openpty
    rcmd
    rcmd_af
    reallocf
    res_close
    res_init
    res_mkquery
    res_nclose
    res_ninit
    res_nmkquery
    res_nquery
    res_nquerydomain
    res_nsearch
    res_nsend
    res_query
    res_querydomain
    res_search
    res_send
    revoke
    rexec
    rpmatch
    rresvport
    rresvport_af
    ruserok
    sbrk
    setbuffer
    setgroups
    sethostname
    setlinebuf
    setpassent
    setprogname
    settimeofday
    setusershell
    statfs
    strcasestr
    strsep
    timingsafe_bcmp
    timingsafe_memcmp
    updwtmp
```

```
valloc
verr
verrx
vhangup     (see chapter "Implementation Notes")
vsyslog
vwarn
vwarnx
wait3
wait4
warn
warnx
```

1.3 System interfaces compatible with GNU or Linux extensions:

```
__mempcpy
argz_add
argz_add_sep
argz_append
argz_count
argz_create
argz_create_sep
argz_delete
argz_extract
argz_insert
argz_next
argz_replace
argz_stringify
asnprintf
asprintf_r
basename      (see chapter "Implementation Notes")
canonicalize_file_name
clearenv
clog10
clog10f
clog10l
close_range     (see chapter "Implementation Notes")
crypt_r     (available in external "libcrypt" library)
dremf
envz_add
envz_entry
envz_get
envz_merge
envz_remove
envz_strip
error
error_at_line
euidaccess
execvpe
exp10
exp10f
exp10l
fallocate     (see chapter "Implementation Notes")
fcloseall
fcloseall_r
fedisableexcept
feenableexcept
fegetexcept
fgets_unlocked
fgetwc_unlocked
```

```
    fgetws_unlocked
    fgetxattr
    flistxattr
    fopencookie
    fputs_unlocked
    fputwc_unlocked
    fputws_unlocked
    fremovexattr
    fsetxattr
    get_avphys_pages
    get_current_dir_name
    get_nprocs
    get_nprocs_conf
    get_phys_pages
    getmntent_r
    getopt_long
    getopt_long_only
    getpt
    getwc_unlocked
    getwchar_unlocked
    getxattr
    lgetxattr
    listxattr
    llistxattr
    lremovexattr
    lsetxattr
    mempcpy
    memrchr
    mkostemps
    posix_spawn_file_actions_addchdir_np
    posix_spawn_file_actions_addfchdir_np
    pow10
    pow10f
    pow10l
    pthread_getaffinity_np
    pthread_getattr_np
    pthread_getname_np
    pthread_setaffinity_np
    pthread_setname_np
    pthread_sigqueue
    pthread_timedjoin_np
    pthread_tryjoin_np
    putwc_unlocked
    putwchar_unlocked
    quotactl
    rawmemchr
    removexattr
    renameat2     (see chapter "Implementation Notes")
    scandirat
    sched_getaffinity
    sched_getcpu
    sched_setaffinity
    setxattr
    signalfd
    sincos
    sincosf
    sincosl
    strchrnul
    strptime_l
    strtod_l
    strtof_l
    strtol_l
```

```
strtold_l
strtoll_l
strtoul_l
strtoull_l
strverscmp
sysinfo
tdestroy
timegm
timelocal
timerfd_create
timerfd_gettime
timerfd_settime
toascii_l
updwtmpx
utmpxname
vasnprintf
vasprintf_r
versionsort
wcsftime_l
wcstod_l
wcstof_l
wcstol_l
wcstold_l
wcstoll_l
wcstoul_l
wcstoull_l
wmempcpy
```

1.4 System interfaces compatible with Solaris or SunOS functions:

```
__fbufsize
__flbf
__fpending
__fpurge
__freadable
__freading
__fsetlocking
__fwritable
__fwriting
__xdrrec_getrec   (available in external "libtirpc" library)
__xdrrec_setnonblock  (available in external "libtirpc" library)
acl       (see chapter "Implementation Notes")
aclcheck      (see chapter "Implementation Notes")
aclfrommode     (see chapter "Implementation Notes")
aclfrompbits    (see chapter "Implementation Notes")
aclfromtext     (see chapter "Implementation Notes")
aclsort     (see chapter "Implementation Notes")
acltomode     (see chapter "Implementation Notes")
acltopbits      (see chapter "Implementation Notes")
acltotext     (see chapter "Implementation Notes")
endmntent
facl      (see chapter "Implementation Notes")
fegetprec
fesetprec
futimesat
getmntent
memalign
setmntent
xdr_array     (available in external "libtirpc" library)
```

```
xdr_bool      (available in external "libtirpc" library)
xdr_bytes     (available in external "libtirpc" library)
xdr_char      (available in external "libtirpc" library)
xdr_double      (available in external "libtirpc" library)
xdr_enum      (available in external "libtirpc" library)
xdr_float     (available in external "libtirpc" library)
xdr_free      (available in external "libtirpc" library)
xdr_hyper     (available in external "libtirpc" library)
xdr_int     (available in external "libtirpc" library)
xdr_int16_t     (available in external "libtirpc" library)
xdr_int32_t     (available in external "libtirpc" library)
xdr_int64_t     (available in external "libtirpc" library)
xdr_int8_t      (available in external "libtirpc" library)
xdr_long      (available in external "libtirpc" library)
xdr_longlong_t    (available in external "libtirpc" library)
xdr_netobj      (available in external "libtirpc" library)
xdr_opaque      (available in external "libtirpc" library)
xdr_pointer     (available in external "libtirpc" library)
xdr_reference   (available in external "libtirpc" library)
xdr_short     (available in external "libtirpc" library)
xdr_sizeof      (available in external "libtirpc" library)
xdr_string      (available in external "libtirpc" library)
xdr_u_char      (available in external "libtirpc" library)
xdr_u_hyper     (available in external "libtirpc" library)
xdr_u_int     (available in external "libtirpc" library)
xdr_u_int16_t   (available in external "libtirpc" library)
xdr_u_int32_t   (available in external "libtirpc" library)
xdr_u_int64_t   (available in external "libtirpc" library)
xdr_u_int8_t    (available in external "libtirpc" library)
xdr_u_long      (available in external "libtirpc" library)
xdr_u_longlong_t    (available in external "libtirpc" library)
xdr_u_short     (available in external "libtirpc" library)
xdr_uint16_t    (available in external "libtirpc" library)
xdr_uint32_t    (available in external "libtirpc" library)
xdr_uint64_t    (available in external "libtirpc" library)
xdr_uint8_t     (available in external "libtirpc" library)
xdr_union     (available in external "libtirpc" library)
xdr_vector      (available in external "libtirpc" library)
xdr_void      (available in external "libtirpc" library)
xdr_wrapstring    (available in external "libtirpc" library)
xdrmem_create   (available in external "libtirpc" library)
xdrrec_create   (available in external "libtirpc" library)
xdrrec_endofrecord    (available in external "libtirpc" library)
xdrrec_eof      (available in external "libtirpc" library)
xdrrec_skiprecord   (available in external "libtirpc" library)
xdrstdio_create   (available in external "libtirpc" library)
```

1.5 System interfaces not in POSIX but compatible with ISO C requirements:

```
c8rtomb     (ISO C23)
mbrtoc8     (ISO C23)
```

1.6 Other UNIX® system interfaces, not in POSIX.1-2024, or deprecated:

```
_longjmp      (SUSv4)
_setjmp     (SUSv4)
```

```
_tolower      (SUSv4)
_toupper      (SUSv4)
acl_add_perm    (POSIX.1e draft)
acl_calc_mask   (POSIX.1e draft)
acl_check     (libacl)
acl_clear_perms   (POSIX.1e draft)
acl_cmp     (libacl)
acl_copy_entry    (POSIX.1e draft)
acl_copy_ext    (POSIX.1e draft)
acl_copy_int    (POSIX.1e draft)
acl_create_entry    (POSIX.1e draft)
acl_delete_def_file   (POSIX.1e draft)
acl_delete_entry    (POSIX.1e draft)
acl_delete_perm   (POSIX.1e draft)
acl_dup     (POSIX.1e draft)
acl_entries     (libacl)
acl_equiv_mode    (libacl)
acl_error     (POSIX.1e draft)
acl_extended_fd   (libacl)
acl_extended_file   (libacl)
acl_extended_file_nofollow  (libacl)
acl_free      (POSIX.1e draft)
acl_from_mode   (libacl)
acl_from_text   (POSIX.1e draft)
acl_get_entry   (POSIX.1e draft)
acl_get_fd      (POSIX.1e draft)
acl_get_file    (POSIX.1e draft)
acl_get_perm    (libacl)
acl_get_permset   (POSIX.1e draft)
acl_get_qualifier   (POSIX.1e draft)
acl_get_tag_type    (POSIX.1e draft)
acl_init      (POSIX.1e draft)
acl_set_fd      (POSIX.1e draft)
acl_set_file    (POSIX.1e draft)
acl_set_permset   (POSIX.1e draft)
acl_set_qualifier   (POSIX.1e draft)
acl_set_tag_type    (POSIX.1e draft)
acl_size      (POSIX.1e draft)
acl_to_any_text   (libacl)
acl_to_text     (POSIX.1e draft)
acl_valid     (POSIX.1e draft)
atoff     (AIX)
bcmp      (POSIX.1-2001, SUSv3)
bcopy     (SUSv3)
bzero     (SUSv3)
chroot      (SUSv2 - see chapter "Implementation Notes")
clock_setres    (QNX, VxWorks - see chapter "Implementation Notes")
cuserid     (POSIX.1-1988, SUSv2)
ecvt      (SUSv3)
endutent      (XPG2)
fcvt      (SUSv3)
ftime     (SUSv3)
ftw       (SUSv4)
gcvt      (SUSv3)
getcontext      (SUSv3)
gethostbyaddr   (SUSv3)
gethostbyname   (SUSv3)
gethostbyname2    (first defined in BIND 4.9.4)
getitimer     (SUSv4 - see chapter "Implementation Notes")
getpass     (SUSv2)
gets      (SUSv4)
gettimeofday    (SUSv4)
```

```
getutent      (XPG2)
getutid     (XPG2)
getutline     (XPG2)
getw      (SVID)
getwd     (SUSv3)
h_errno     (SUSv3)
index     (SUSv3)
ioctl     (SUSv4)
isascii     (SUSv4)
makecontext     (SUSv3)
mallinfo      (SVID)
mallopt     (SVID)
mktemp      (SUSv3)
on_exit     (SunOS)
pthread_attr_getstackaddr (SUSv3)
pthread_attr_setstackaddr (SUSv3)
pthread_continue    (XPG2)
pthread_getconcurrency  (SUSv4)
pthread_getsequence_np  (Tru64)
pthread_setconcurrency  (SUSv4)
pthread_suspend   (XPG2)
pthread_yield   (POSIX.1c drafts)
pututline     (XPG2)
putw      (SVID)
rand_r      (SUSv4)
rindex      (SUSv3)
scalb     (SUSv3)
setcontext      (SUSv3)
setitimer     (SUSv4 - see chapter "Implementation Notes")
setpgrp     (SUSv4)
setutent      (XPG2)
sighold     (SUSv4)
sigignore     (SUSv4)
siginterrupt    (SUSv4)
sigpause      (SUSv4 - see chapter "Implementation Notes")
sigrelse      (SUSv4)
sigset      (SUSv4)
stime     (SVID)
swapcontext     (SUSv3)
sys_errlist     (BSD)
sys_nerr      (BSD)
sys_siglist     (BSD)
tempnam     (SUSv4)
toascii     (SUSv4)
ttyslot     (SUSv2)
ualarm      (SUSv3)
usleep      (SUSv3)
utime     (SUSv4)
utmpname      (XPG2)
vfork     (SUSv3 - see chapter "Implementation Notes")
```

1.7 NOT implemented system interfaces from the Single UNIX® Specification Version 5:

```
_Fork
dcgettext_l
dcngettext_l
dgettext_l
dngettext_l
```

```
endnetent
fmtmsg
getdate
getdate_err
gethostent
getnetbyaddr
getnetbyname
getnetent
getresgid
getresuid
gettext_l
mlockall
munlockall
ngettext_l
posix_mem_offset
posix_typed_mem_get_info
posix_typed_mem_open
pthread_mutex_consistent
pthread_mutexattr_getrobust
pthread_mutexattr_setrobust
setnetent
setresgid
setresuid
waitid
```

1.8 Other system interfaces, some from Windows:

```
_get_osfhandle              (Windows)
_setmode                    (Windows)
cwait                       (Windows)
cygwin_attach_handle_to_fd
cygwin_conv_path
cygwin_conv_path_list
cygwin_create_path
cygwin_detach_dll
cygwin_dll_init
cygwin_internal
cygwin_logon_user
cygwin_posix_path_list_p
cygwin_set_impersonation_token
cygwin_split_path
cygwin_stackdump
cygwin_umount
cygwin_winpid_to_pid
spawnl                      (Windows)
spawnle                     (Windows)
spawnlp                     (Windows)
spawnlpe                    (Windows)
spawnv                      (Windows)
spawnve                     (Windows)
spawnvp                     (Windows)
spawnvpe                    (Windows)
```

1.9 Implementation Notes

`chroot` only emulates a chroot function call by keeping track of the current root and accomodating this in the file related function calls. A real chroot functionality is not supported by Windows however.

clock_nanosleep currently supports only CLOCK_REALTIME and CLOCK_MONOTONIC. clock_setres, clock_settin and timer_create currently support only CLOCK_REALTIME.

close_range does not support the Linux-specific flag CLOSE_RANGE_UNSHARE.

The Solaris-invented ACL functions acl, facl, aclcheck, aclfrommode, aclfrompbits, aclfromtext, aclsort, acltomode, acltopbits and acltotext and the belonging macros and datatypes are defined in <cygwin/acl.h> since they collide with the Linux-compatible POSIX.1e draft macros in <sys/acl.h>. Just include <cygwin/acl.h> if you prefer them over the POSIX.1e functions.

POSIX file locks via fcntl or lockf, as well as BSD flock locks are advisory locks. They don't interact with Windows mandatory locks, nor do POSIX fcntl locks interfere with BSD flock locks or vice versa.

BSD file locks created via flock are only propagated to the direct parent process, not to grand parents or sibling processes. The locks are only valid in the creating process, its parent process, and subsequently started child processes sharing the same file descriptor.

In very rare circumstances an application would want to use Windows mandatory locks to interact with non-Cygwin Windows processes accessing the same file (databases, etc). For these purposes, the entire locking mechanism (fcntl/flock/lockf) can be switched to Windows mandatory locks on a per-descriptor/per-process basis. For this purpose, use the call

```
fcntl (fd, F_LCK_MANDATORY, 1);
```

After that, all file locks on this descriptor will follow Windows mandatory record locking semantics: Locks are per-descriptor/per-process; locks are not propagated to child processes, not even via execve; no atomic replacement of read locks with write locks and vice versa on the same descriptor; locks have to be unlocked exactly as they have been locked.

fpclassify, isfinite, isgreater, isgreaterequal, isinf, isless, islessequal, islessgreater, isnan, isnormal, isunordered, and signbit only support float and double arguments, not long double arguments.

getitimer and setitimer only support ITIMER_REAL for now.

link will fail on FAT, FAT32, and other filesystems not supporting hardlinks, just as on Linux.

lseek only works properly on files opened in binary mode. On files opened in textmode (via mount mode or explicit open flag) its positioning is potentially unreliable.

setuid is only safe against reverting the user switch after a call to one of the exec(2) functions took place. Windows doesn't support a non-revertable user switch within the context of Win32 processes.

vfork just calls fork.

vhangup and revoke always return -1 and set errno to ENOSYS. grantpt and unlockpt always just return 0.

The XSI IPC functions semctl, semget, semop, shmat, shmctl, shmdt, shmget, msgctl, msgget, msgrcv and msgsnd are only available when cygserver is running.

The Linux-specific function quotactl only implements what works on Windows: Windows only supports user block quotas on NTFS, no group quotas, no inode quotas, no time constraints.

qsort_r is available in both BSD and GNU flavors, depending on whether _BSD_SOURCE or _GNU_SOURCE is defined when compiling.

The Linux-specific function renameat2 only supports the RENAME_NOREPLACE flag.

basename is available in both POSIX and GNU flavors, depending on whether libgen.h is included or not.

sigpause is available in both BSD and SysV/XSI flavors, depending on whether _XOPEN_SOURCE is defined when compiling.

strerror_r is available in both POSIX and GNU flavors, depending on whether _GNU_SOURCE is defined when compiling.

dladdr always sets the Dl_info members dli_sname and dli_saddr to NULL, indicating no symbol matching addr could be found.

getrlimit resources RLIMIT_AS, RLIMIT_CPU, RLIMIT_FSIZE, RLIMIT_DATA always return rlim_cur and rlim_max as RLIM_INFINITY, so setrlimit returns -1 and sets EINVAL if they are lowered, or returns 0 if unchanged. getrlimit resource RLIMIT_NOFILE always returns rlim_cur and rlim_max as OPEN_MAX; setrlimit returns 0 sets EINVAL if

rlim_cur > rlim_max, does not change the value if it is RLIM_INFINITY, otherwise returns the result from `setdtablesize`. `getrlimit`/`setrlimit` resources RLIMIT_CORE and RLIMIT_STACK return the current values and set the requested values. All other resource arguments return -1 and set EINVAL.

`fallocate` has a few Windows quirks: The FALLOC_FL_ZERO_RANGE operation is NOT atomic. With flags set to 0 and FALLOC_FL_KEEP_SIZE, sparse blocks in the given range are re-allocated as per the POSIX requirements. This re-allocation operation isn't atomic either. Over-allocation with FALLOC_FL_KEEP_SIZE is only temporary on Windows until the last handle to the file is closed. Over-allocation on sparse files is entirely ignored on Windows.

`sched_setscheduler` only emulates API behavior because Windows does not offer alternative scheduling policies. If `SCHED_OTHER` or `SCHED_BATCH` is selected, the Windows priority is set according to the nice value. If `SCHED_IDLE` is selected, the Windows priority is set to `IDLE_PRIORITY_CLASS`. If `SCHED_FIFO` or `SCHED_RR` is selected, the nice value is preserved and the Windows priority is set according to the `sched_priority` value. If the `SCHED_RESET_ON_FORK` flag is set, realtime policies and negative nice values are dropped on `fork`.

`nice`, `setpriority`, `sched_setparam` and `sched_setscheduler` map the nice value (`SCHED_OTHER`, `SCHED_BATCH`) or the `sched_priority` (`SCHED_FIFO`, `SCHED_RR`) to Windows priority classes as follows:

```
SCHED_OTHER  SCHED_BATCH  SCHED_FIFO/RR
nice value   nice value   sched_priority   Windows priority class
 12...19       4...19      1....6          IDLE_PRIORITY_CLASS
  4...11      -4....3      7...12          BELOW_NORMAL_PRIORITY_CLASS
 -4....3     -12...-5     13...18          NORMAL_PRIORITY_CLASS
-12...-5     -13..-19     19...24          ABOVE_NORMAL_PRIORITY_CLASS
-13..-19          -20     25...30          HIGH_PRIORITY_CLASS
     -20            -     31...32          REALTIME_PRIORITY_CLASS
```

The use of values which are mapped to the `REALTIME_PRIORITY_CLASS` require administrative privileges.

Chapter 2

Cygwin Functions

These functions are specific to Cygwin itself, and probably won't be found anywhere else.

2.1 Path conversion functions

2.1.1 cygwin_conv_path

cygwin_conv_path

Synopsis

```
#include <sys/cygwin.h>
```

ssize_t **cygwin_conv_path**(cygwin_conv_path_t what, const void * from, void * to, size_t size);

Description

Use this function to convert POSIX paths in *from* to Win32 paths in *to* or, vice versa, Win32 paths in *from* to POSIX paths in *to*. *what* defines the direction of this conversion and can be any of the below values.

```
CCP_POSIX_TO_WIN_A      /* from is char *posix, to is char *win32       */
CCP_POSIX_TO_WIN_W,     /* from is char *posix, to is wchar_t *win32    */
CCP_WIN_A_TO_POSIX,     /* from is char *win32, to is char *posix       */
CCP_WIN_W_TO_POSIX,     /* from is wchar_t *win32, to is char *posix    */
```

You can additionally or the following values to *what*, to define whether you want the resulting path in *to* to be absolute or if you want to keep relative paths in relative notation. Creating absolute paths is the default.

```
CCP_ABSOLUTE = 0,         /* Request absolute path (default).             */
CCP_RELATIVE = 0x100      /* Request to keep path relative.               */
CCP_PROC_CYGDRIVE = 0x200 /* Request to return /proc/cygdrive path
                             (only with CCP_*_TO_POSIX).                  */
```

size is the size of the buffer pointed to by *to* in bytes. If *size* is 0, cygwin_conv_path just returns the required buffer size in bytes. Otherwise, it returns 0 on success, or -1 on error and errno is set to one of the below values.

```
  EINVAL        what has an invalid value or from is NULL.
  EFAULT        from or to point into nirvana.
  ENAMETOOLONG  the resulting path is longer than 32K, or, in case
                of what == CCP_POSIX_TO_WIN_A, longer than MAX_PATH.
  ENOSPC        size is less than required for the conversion.
```

Example

Example 2.1 Example use of cygwin_conv_path

```
#include <sys/cygwin.h>

/* Conversion from incoming Win32 path given as wchar_t *win32 to POSIX path.
   If incoming path is a relative path, stick to it.  First ask how big
   the output buffer has to be and allocate space dynamically. */
ssize_t size;
char *posix;
size = cygwin_conv_path (CCP_WIN_W_TO_POSIX | CCP_RELATIVE, win32, NULL, 0);
if (size < 0)
  perror ("cygwin_conv_path");
else
  {
    posix = (char *) malloc (size);
    if (cygwin_conv_path (CCP_WIN_W_TO_POSIX | CCP_RELATIVE, win32,
                          posix, size))
      perror ("cygwin_conv_path");
  }
```

2.1.2 cygwin_conv_path_list

cygwin_conv_path_list

Synopsis

```
#include <sys/cygwin.h>
```

ssize_t **cygwin_conv_path_list**(cygwin_conv_path_t what, const void * from, void * to, size_t size);

Description

This is the same as `cygwin_conv_path`, but the input is treated as a path list in $PATH or %PATH% notation.

If *`what`* is CCP_POSIX_TO_WIN_A or CCP_POSIX_TO_WIN_W, given a POSIX $PATH-style string (i.e. /foo:/bar) convert it to the equivalent Win32 %PATH%-style string (i.e. d:\;e:\bar).

If *`what`* is CCP_WIN_A_TO_POSIX or CCP_WIN_W_TO_POSIX, given a Win32 %PATH%-style string (i.e. d:\;e:\bar) convert it to the equivalent POSIX $PATH-style string (i.e. /foo:/bar).

`size` is the size of the buffer pointed to by *`to`* in bytes.

See also

See also cygwin_conv_path

2.1.3 cygwin_create_path

cygwin_create_path

Synopsis

```
#include <sys/cygwin.h>
```

void * **cygwin_create_path**(cygwin_conv_path_t what, const void * from);

Description

This is equivalent to the `cygwin_conv_path`, except that `cygwin_create_path` does not take a buffer pointer for the result of the conversion as input. Rather it allocates the buffer itself using `malloc`(3) and returns a pointer to this buffer. In case of error it returns NULL and sets errno to one of the values defined for `cygwin_conv_path`. Additionally errno can be set to the below value.

```
    ENOMEM        Insufficient memory was available.
```

When you don't need the returned buffer anymore, use `free`(3) to deallocate it.

See also

See also cygwin_conv_path

2.1.4 cygwin_posix_path_list_p

cygwin_posix_path_list_p

Synopsis

```
#include <sys/cygwin.h>
```

int **cygwin_posix_path_list_p**(const char *path);

Description

This function tells you if the supplied *`path`* is a POSIX-style path (i.e. posix names, forward slashes, colon delimiters) or a Win32-style path (drive letters, reverse slashes, semicolon delimiters. The return value is true if the path is a POSIX path. Note that "_p" means "predicate", a lisp term meaning that the function tells you something about the parameter.

2.1.5 cygwin_split_path

cygwin_split_path

Synopsis

```
#include <sys/cygwin.h>
```

void **cygwin_split_path** (const char * path, char * dir, char * file);

Description

Split a path into the directory and the file portions. Both *`dir`* and *`file`* are expected to point to buffers of sufficient size.

Example

Example 2.2 Example use of cygwin_split_path

```
char dir[200], file[100];
cygwin_split_path("c:/foo/bar.c", dir, file);
printf("dir=%s, file=%s\n", dir, file);
```

2.2 Helper functions to change user context

2.2.1 cygwin_logon_user

cygwin_logon_user

Synopsis

```
#include <sys/cygwin.h>
```

HANDLE **cygwin_logon_user**(const struct passwd *passwd_entry, const char *password);

Description

Given a pointer to a passwd entry of a user and a cleartext password, returns a HANDLE to an impersonation token for this user which can be used in a subsequent call to `cygwin_set_impersonation_token` to impersonate that user. This function can only be called from a process which has the required NT user rights to perform a logon.

See also

See also the chapter Switching the user context in the Cygwin User's guide.

See also cygwin_set_impersonation_token

2.2.2 cygwin_set_impersonation_token

cygwin_set_impersonation_token

Synopsis

```
#include <sys/cygwin.h>
```

void **cygwin_set_impersonation_token**(const HANDLE token);

Description

Use this function to enable the token given as parameter as impersonation token for the next call to `setuid` or `seteuid`. Use `cygwin_set_impersonation_token` together with `cygwin_logon_user` to impersonate users using password authentication.

See also

See also the chapter Switching the user context in the Cygwin User's guide.

See also cygwin_logon_user

2.3 Miscellaneous functions

2.3.1 cygwin_attach_handle_to_fd

cygwin_attach_handle_to_fd

Synopsis

```
#include <sys/cygwin.h>
```

int **cygwin_attach_handle_to_fd**(char *name, int fd, HANDLE handle, int bin, int access);

Description

This function can be used to turn a Win32 "handle" into a posix-style file handle. *fd* may be -1 to make cygwin allocate a handle; the actual handle is returned in all cases.

Even after using function, Cygwin doesn't know anything about the underlying file or device. It just tries to supply the typical file functions on a "best-effort" basis. Use with care. Don't expect too much.

2.3.2 cygwin_internal

cygwin_internal

Synopsis

```
#include <sys/cygwin.h>
```

uintptr_t **cygwin_internal**(cygwin_getinfo_types t, ...);

Description

This function gives you access to various internal data and functions. It takes two arguments. The first argument is a type from the 'cygwin_getinfo_types' enum. The second is an optional pointer.

Stay away unless you know what you're doing.

2.3.3 cygwin_stackdump

cygwin_stackdump

Synopsis

```
#include <sys/cygwin.h>
```

void **cygwin_stackdump**(void);

Description

Outputs a stackdump to stderr from the called location.

Note: This function only has an effect the first time it is called by a process.

Note: This function is deprecated.